

Model		TWH09AT19D6DI
INDOOR UNIT		
Air Flow (Min-Max)	CFM	159 - 353
Sound Pressure Level	dB(A)	24 - 41
Dehumidification	pt/hr	1.69
Indoor Unit Dimension (WxHxD)	in	32-7/8 × 10-53/64 × 7-7/8
Package Dimension (WxHxD)	in	35-15/64 × 13-37/64 × 10-43/64
Net Weight	lb	19.8
Gross Weight	lb	24.3
REFRIGERANT PIPING		
Refrigerant Charge	oz	18.7
Additional Charge	oz/ft	0.2
Line Set Size (Liquid - Gas) - Flared Connections	in	1/4 - 3/8
Pre-Charge Length	ft	25
Pipe Length (Min - Max)	ft	10 - 66
Max Pipe Elevation	ft	40
ELECTRICAL		
Power Supply	208-230 / 1Ph / 60Hz (Powered by Outdoor Unit)	
Voltage Range (Min - Max)	VAC	187 - 253
Rated Current - Cooling	A	6.5
Rated Current - Heating	A	7
MCA	A	10
MOCP	A	15
Main Power Wire Size	AWG	Per Local Code
Interconnecting Wire Size	AWG	14/4

TWH09AT19D6DI Dimensions (in)

W	32 7/8
H	10 53/64
D	7 7/8
W1	7 1/64
W2	18 3/16
W3	7 43/64

